




Access Control Cable

**18AWG 4C + 22AWG 2C + 22AWG 4C + 22AWG 3PAIR SHLD
CMR(Riser Rated)**

Cable Structure



Standard & Application

c(ETL)	Indoor Communication
CE	Remote Control
RoHS	Signalling

Construction

- Conductor: Bare Copper
- Insulation: Premium grade, color-coded PVC
- Rip cord: A nylon rip cord under jacket for ease of jacket stripping
- Shield: Overall polyester backed aluminum foil, with 26AWG tinned copper drain wire
- Jacket: Premium grade green PVC jacket

Specifications

P/N	Overall Nominal O.D.	Comp.No.	Comp. Desc.	Cond Colors	Comp.No minal O.D.	Ins. Thickness
RCOMBO16C-GN	.480	1	18AWG 4 COND	White	.190	.008
				Red		
				Black		
				Green		
		2	22AWG 3PR	Black/Red	.225	.007
				White/Green		
				Brown/Orange		
		3	22AWG 2	Black	.132	.007
				Red		
		4	22AWG 4 COND	White	.154	.007
				Black		
				Red		
				Green		

Electrical Performance

Conductor DC Resistance at 20°C	
22AWG	≤55.4Ω/km
18AWG	≤21.9Ω/km
Voltage Rating:	300V

Applications

- Card Readers
- Locking Power
- Door Contacts
- Retina Scanners

Temperature Range

Temp Rating:	75°C
Operation Temperature	-20°C To +75°C

Color Code Chart

Cond	Color
1	Gray/Purple
2	Gray/Yellow
3	Gray/Green
4	Gray/Red

Packing

1,000' Wooden Reel /pallet



Printing:

18AWGx4C : PSI DATA CONTROL CABLE 18AWG 4C UNSHLD 75C c(ETL)us TYPE CMR xxxxxx FT4 "ROHS" DOOR/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 0000FT

22AWGx4C : PSI DATA CONTROL CABLE 22AWG 4C UNSHLD 75C c(ETL)us TYPE CMR xxxxxx FT4 "ROHS" DOOR/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 0000FT

22AWGx2C : PSI DATA CONTROL CABLE 22AWG 2C UNSHLD 75C c(ETL)us TYPE CMR xxxxxx FT4 "ROHS" DOOR/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 0000FT

22AWGx3P : PSI DATA CONTROL CABLE 22AWG 3PAIR SHLD 75C c(ETL)us TYPE CMR xxxxxx FT4 "ROHS" DOOR/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 0000FT

ACCESS CONTROL CABLE: PSI DATA ACCESS CONTROL CABLE 18AWG 4C + 22AWG 2C + 22AWG 4C + 22AWG 3PAIR SHLD 75C c(ETL)us TYPE CMR xxxxx FT4 "ROHS" DOOR/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 0000FT/1000FT

Remarks:

The information on this document is, to our knowledge, true and accurate. However, since the particular uses and the actual conditions of use of our products are beyond our control, establishing satisfactory performance of our products for the intended application is the customer's sole responsibility. All uses of PSI products and any written or oral information, suggestions or technical advice from PSI is without warranty, express or implied, and is not an inducement to use any product in conflict with any patent.