




LAN CABLE

5EODB-SH

Outdoor Direct Burial

Cable Structure



Electrical Performance (20 °C)

1.0-100.0 MHz Impedance (Ω) 100±15
 1.0-100.0 MHz Delay Shew (ns / 100m) ≤45
 Max DC Resistance (Ω / 100m) 9.5
 Max DC Conductor Resistance Unbalance (%) 5.0
 Voltage Rating: 80V

Temperature Range

Temp Rating: 90°C
 Operation Temperature -20°C To +90°C

Technical Performance

MHz	RL ≥ dB	ATT ≤ dB	NEXT ≥ dB	PSNEXT ≥ dB
1	17	2.2	60	57
4	17	4.5	53.5	50.5
8	17	6.3	48.6	45.6
10	17	7.1	47	44
16	17	9.1	43.6	40.6
20	17	10.2	42	39
25	16	11.4	40.3	37.3
31.25	15.1	12.9	38.7	35.7
62.5	12.1	18.6	33.6	30.6
100	10	24	30.1	27.1
*200	9.0	34.4	25.8	22.8
*300	8.5	43.8	24.3	21.3
*350	8.0	46.9	22.1	19.1

Test Standard

ISO / IEC 11801
 ANSI / TIA-568.2-D

Construction & Specifications

- Conductor: Solid-Bare Copper 0.50±0.05mm
- Insulation: High Density Polyethylene HDPE 0.95±0.03mm
 1. Blue & White with Blue
 2. Orange & White with Orange
 3. Green & White with Green
 4. Brown & White with Brown
- Insulation Color:
- Wrap 1 : Polyester Film PET
- Wrap 2 : Water Block Tape
- Drain wire : Tinned copper 7x0.12±0.008mm
- Shield: Overall polyester backed aluminum foil
- Rid cord: A nylon rip cord under jacket for ease of jacket stripping
- Jacket: Polyethylene Black PE jacket 6.5±0.20mm

Jacket Physical Properties

Before Aging Tensile Strength (MPa) ≥ 9.7
 Before Aging Elongation (%) ≥ 300
 Aging Period (°C x hrs) 100°C x 24h x 2d
 After Aging Tensile Strength (MPa) ≥ 7.25
 After Aging Elongation (%) ≥ 225

Printing:

PSI DATA OUTDOOR FTP CAT5e OSP 350MHz 4PR 24 AWG VERIFIED TO ANSI/TIA - 568.2-D CAT 5e DB UV RoHS 0000FT/1000FT

Remarks:

The information on this document is, to our knowledge, true and accurate. However, since the particular uses and the actual conditions of use of our products are beyond our control, establishing satisfactory performance of our products for the intended application is the customer's sole responsibility. All uses of PSI products and any written or oral information, suggestions or technical advice from PSI is without warranty, express or implied, and is not an inducement to use any product in conflict with any patent.

Packing

1,000' Reel / /pallet

