




## Station "Z" Cable ZSTNCMP CMP(Plenum Rated)

### Cable Structure



### Electrical Performance

Conductor DC Resistance at 20°C  
22AWG ≤55.4Ω/km  
Voltage Rating: 300V

### Applications

- Security Systems
- Sound / Audio System
- Intercom Systems
- Power-Limited Controls

### Temperature Range

Temp Rating: 75°C  
Operation Temperature -20°C To +75°C

### Color Code Chart

Cond	Color	Cond	Color
1	Black	3	Green
2	Red	4	Yellow

### Standard & Application

c(ETL) door Communication  
CE Remote Control  
RoHS Signalling

### Construction

- Conductor:Bare Copper
- Insulation: Premium grade,color-coded PVC
- Rid cord: A nylon rip cord under jacket for ease of jacket stripping
- Jacket: Low Smoke white PVC jacket

### Specifications

P/N	Size(AWG)	No.of Conductors	Stranding	Nominal Thickness		Nominal Overall Diameter (inches)
				Insulation	Jacket	
ZSTNCMP-WH	22	4	1	.008'	.024'	0.129

### Packing

1,000' Pull Boxes/ /pallet



### Printing:

PSI DATA 22AWG 4C SOL PLENUM CABLE c(ETL)us TYPE CMP xxxxxxx FT6 0000FT/1000FT

### Remarks:

The information on this document is, to our knowledge, true and accurate. However, since the particular uses and the actual conditions of use of our products are beyond our control, establishing satisfactory performance of our products for the intended application is the customer's sole responsibility. All uses of PSI products and any written or oral information, suggestions or technical advice from PSI is without warranty, express or implied, and is not an inducement to use any product in conflict with any patent.